



# Aspirateurs



TYPE	Dimensions intérieures	Nombre de pieds	Poids Unitaire	Nbre palette
Base Bandeau+Cape	<b>20X20</b>	3	29 kg	27
Base bandeau			12 kg	
Cape			17 kg	
Base Bandeau+Cape	<b>25X25</b>	3	30 kg	12
Base bandeau			12 kg	
Cape			18 kg	
Base Bandeau+Cape	<b>20X40</b>	4	35 kg	18
Base Bandeau			13 kg	
Cape			22 kg	
Base Bandeau+Cape	<b>30X30</b>	4	37 kg	12
Base Bandeau			13 kg	
Cape			24 kg	
Base Bandeau+Cape	<b>25X50</b>	4	50,5 kg	9
Base Bandeau			18,5 kg	
Cape			32 kg	
Base Bandeau+Cape	<b>30X50</b>	4	52 kg	9
Base Bandeau			19 kg	
Cape			33 kg	
Base Bandeau+Cape	<b>35X35</b>	4	48 kg	12
Base Bandeau			16 kg	
Cape			32 kg	

★ Améliore les performances des cheminées





# Boisseaux



Désignation	Section intérieure cm <sup>2</sup>	Hauteur élément cm	Dimensions extérieures cm	Ø hydraulique cm	épaisseur parois mm	Poids unitaire Kg	Nb par palette	Classe de température	
16x16X25 T300	241	25	23,6x23,6	16,2	40	14	80	T300	
16X20 20X20/25	317+420	25	29,6X49,6	18,5+21	40	32	80	T300	T450
20X20X25	420	25	29,6x29,6	21	45	21	54	T300	T450
20X40X25	809	25	29,6x49,6	27	45	29	54	T300	T450
25X25X25	600	25	35X35	25	50	27	54	T300	T450
30X30X25	870	25	40X40	30	50	31	54	T300	T450
30X50X25	1460	25	40X60	37	50	42	24	T300	T450
35X35X25	1190	25	45X45	35	50	36	24	T300	T450

Produit conforme au référentiel de certification NF 054 Conduit de fumée en Béton, et aux normes NF EN 1857, NF EN 1858, NF EN 12446.

## T300 - T450

- ★ Mise en oeuvre traditionnelle conforme aux exigences du DTU 24.1
- ★ Béton de Pouzzolane très performant

