

# BLOCS CREUX

	CARACTERISTIQUES					TYPES D'OUVRAGES					
	Longueur mm	Largeur mm	Hauteur mm	Poids unité	Nb palette	Facades	Rebords	Soubassements enterrés	Murs séparatifs de logement	cloisons	Rives de plancher
<b>500X45X200</b>	500	45	200	8	180					😊	😊
<b>500X75X200</b>	500	75	200	8	144*					😊	
<b>500X100X200</b>	500	100	200	9	120*					😊	
<b>500X150X200 1 LAME</b>	500	150	200	11	98	😊					
<b>500X150X200 2 LAMES</b>	500	150	200	13	84	😊					
<b>500X200X200 40 BARS</b>	500	200	200	15	70*	😊	😊	😊			
<b>500X200X200 60 BARS</b>	500	200	200	15	70	😊	😊	😊			
<b>500X150X250</b>	500	150	250	18	70	😊					
<b>500X250X200</b>	500	250	200	21	56	😊	😊	😊			
<b>500X275X200</b>	500	275	200	22	48	😊	😊	😊			
<b>500X200X200 À EMBOITEMENT</b>	500	200	200	16	70	😊	😊	😊			
<b>500X200X250 À EMBOITEMENT</b>	500	200	250	21	60 *	😊	😊	😊			

\* peut varier selon l'usine

😊 Type d'ouvrage approprié